QUICK REFERENCE GUIDE > HC60BCXB2

Wall Cooker Hood, 60cm, Box Chimney

Series 7 | Contemporary

Stainless Steel and Glass



The wall chimney cooker hood has a contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.


- With four fan speeds, plus boost function, select the perfect extraction rate for your cooking
- Powerful maximum air movement 710m³/hr
- Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

 Height
 600 - 1035 mm

 Width
 600 mm

 Depth
 500 mm



FEATURES & BENEFITS

Effective and quiet

This cooker hood features four fan speeds, plus a boost function, providing powerful extraction to quickly remove odours and steam. As odours can linger in the kitchen well after cooking is finished, the timer keeps the cooker hood working for up to 15 minutes before automatically turning off.

Simple to use

This Fisher & Paykel chimney cooker hood features a sleek and easy to use touch-control panel. Low energy, dimmable LED

lights provide superb illumination over the entire cooking surface.

Easy cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe. The stainless steel mesh cover just needs a quick wipe to keep clean. An alert reminds you when to clean the filter to ensure you get the best performance out of your cooker hood.

Designed to match

This wall cooker hood features sleek black glass and stainless steel styling which will complement any contemporary kitchen and is designed to match the rest of Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Maximum motor performance

Maximum sound rating

Accessories Aluminium filter Chimney extension Eave ducting kit Light bulb Recirculation carbon filter Recirculation diverter Side wall ducting kit Consumption	791938 792492 RHK150E 792556 792481
Chimney extension Eave ducting kit Light bulb Recirculation carbon filter Recirculation diverter	792492 RHK150E 792556
Eave ducting kit Light bulb Recirculation carbon filter Recirculation diverter Side wall ducting kit	RHK150E 792556
Light bulb Recirculation carbon filter Recirculation diverter Side wall ducting kit	792556
Recirculation carbon filter Recirculation diverter Side wall ducting kit	
Recirculation diverter Side wall ducting kit	792481
Side wall ducting kit	
	792560
Consumption	RHK150W
Energy rating	В
Fan ratings	
Maximum air movement	636m³/hr

1100m3/hr

69dBA

FISHER & PAYKEL

QUICK REFERENCE GUIDE > HC60BCXB2 Date: 08.04.2021 > 2

Maximum sound rating at	69dBA
Installation and cleaning	
Air outlet size	150mm
Dishwasher safe filters	2
Ducted	Top extraction
Recirculation	Optional - top extraction
Stainless steel filter cover	•
Two piece height adjustable	•
Performance	
Airflow balancing plate	•
Extraction type	Surface
Fan speeds	4 plus boost
Filter type	Mesh with Stainless Steel filter
Number of filters	2
Power requirements	
Lighting power	7W
Motor power	130W
Rated current	3A
Supply frequency	50Hz
Supply voltage	220-240V
Total Power	137W
Product dimensions	
Depth	500 mm

Height Width 600 - 1035 mm

600 mm

Capacitive-touch
•
LED 2 x 4W
•
5 years

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide



Resources (zip)

