

iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

C



Optional accessories

LZ55750	
LZ55651	
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11ITD11	
LZ10ITP00	

The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Fast-acting extraction for sudden bursts of steam - Intensive Setting

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 8.963
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 630
 Boost position output recirculating (m³/h) : 310.0
 Maximum output recirculating air (m³/h) : 300
 Boost position air extraction (m³/h) : 730
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 66
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003686263
 Connection rating (W) : 277
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in



iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

Features

Key Information

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- 2 x 1W LED lights
- 2 x metal grease filter cassettes
- Steel filter cover, Steel filter cover
- Rim ventilation

Design

- 70 cm wide
- Stainless Steel
- For installation in a kitchen cabinet
- Electronic control via Soft touch button control
- White electronic display

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 630 m³/h
 - Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 66 dB(A) re 1 pW
 - Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode:
 - Max. normal use: 571 m³/h
 - Intensive: 664 m³/h
 - Noise level in recirculation mode:
 - Max. normal use: 72 dB(A) re 1 pW
 - Intensive: 75 dB(A) re 1 pW
- Power rating: 277 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Dimensions (WxD): 700 x 300 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Average Energy Consumption: 104.2 kWh/year*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*

* In accordance with the EU-Regulation No 65/2014

**iQ500, Canopy cooker hood, 70 cm,
Stainless steel
LB78574GB**

Dimensioned drawings

