

iQ700, Induction hob, 90 cm, Black EX975LVV1E











Optional accessories

<code>HZ9SE030</code> : Set of 2 pots and 1 pan , <code>HZ9LP200</code> : Pot Ø 18 (bottom) / 20 cm (top) , <code>HZ9LP160</code> : Pot Ø 14 (bottom) / 16 cm (top) , <code>HZ9CF260</code> : Pan Ø 22 / 26 cm , <code>HZ394301</code> : Connecting strip , <code>HZ390522</code> : Griddle Plate , <code>HZ390512</code> : Teppan Yaki (large) , <code>HZ390230</code> : System pan diameter 21cm , <code>HZ390220</code> : System pan diameter 19 cm , <code>HZ390210</code> : System pan diameter 15 cm , <code>HZ390012</code> : Steaming Rack for Stainless Steel roaste , <code>HZ390011</code> : Stainless Steel roaster with glas lid

Siemens flexInduction cooktop is designed for greater flexibility when cooking

- ✓ Always the optimal cooking zone for your cookware flexInduction
- ✓ Space for extra-large pots and pans thanks to the extendable 32
 cm three-ring cooking zone.
- ✓ Select and join the cooking zones with one neatly arranged interface Dual light slider.
- ✓ Home Connect: Information about your cooktop, no matter where you are via smartphone or tablet.
- ✓ The fryingSensor plus controls the temperature in the pan

Feature

Technical Data

Product name/family: Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : 51 x 880-880 x 490-500

Width of the appliance : 912 Dimensions : 51 x 912 x 520

Dimensions of the packed product (HxWxD) (mm) : $126 \times 1073 \times 603$

Net weight (kg): 20.845 Gross weight (kg): 22.7 Residual heat indicator: Separate Location of control panel: Hob front Basic surface material: Ceramic Color of surface: Black

Approval certificates : AENOR, CE Length of electrical supply cord (cm) : 110

EAN code: 4242003759783 Electrical connection rating (W): 11100

Voltage (V): 220-240 Frequency (Hz): 60; 50





iQ700, Induction hob, 90 cm, Black EX975LVV1E

Feature:

Control

- Dual lightSlider
- fryingSensor plus with 5 temperature settings

Design

- 912 mm
- Stainless Steel side trim with bevelled front edge

Special features

- Triple ring zone, 2 flexInduction zones
- 5 induction cooking zones
- Home Connect enables Remote Monitoring no matter where you are, with the easy-to-use Home Connect App
- cookConnect hood control (with Wi-Fi enabled hood)
- powerMove plus
- quickStart function
- reStart function
- Timer for all zones
- Acoustic signal
- Count up timer
- Keep warm function
- 17 power levels
- Power boost setting
- nanDoost setting
- panBoost
- Energy Consumption Display

Safety Features

- Automatic pan recognition
- Automatic safety switch off
- Control panel lock
- Control panel pause
- •
- 2 stage residual heat indicators
- Main on/off switch

Power and size

Cooking zones: 1 x Ø 400 mmx230 mm, 3.3 KW (max. Power levels 3.7 KW) Induction or 2 x Ø 200 mm, 2.2 KW (max. Power levels 3.7 KW) Induction; 1 x Ø 400 mmx230 mm, 3.3 KW (max. Power levels 3.7 KW) Induction or 2 x Ø 200 mm, 2.2 KW (max. Power levels 3.7 KW) Induction

Technical information

- Min. worktop thickness: 16 mm
- Connected load: 11.1 KW
- Connection cable 110 cm
- Cable included in packaging



iQ700, Induction hob, 90 cm, Black EX975LVV1E

