

iQ500, Built-in double oven, Stainless steel **MB535A0S0B**













| HZ915003 | Glass roasting dish, 5,4 L |
|----------|---------------------------------------|
| HZ638300 | 3 level telescopic rails, full ext |
| HZ634000 | Baking and roasting grid (standard) |
| HZ538000 | varioClip rail |
| HZ531010 | Baking tray, non-stick ceramic coated |

Baking tray, grey enamelled HZ327000 Baking stone

HZ531000

- ✓ fast preheat: reach the required cooking temperature sooner.
- ✓ ecoClean Plus: effortless cleaning thanks to a special coating inside the oven that automatically disintegrates dirt and reduces odours significantly.
- ✓ cookControl10: automatic programs ensure best results.
- ✓ lightControl: intuitive operation thanks to the illuminated dial.
- ✓ 3D hotAir: perfect baking results on up to 3 shelves thanks to innovative heat distribution.

Technical Data

Color / Material Front : Stainless steel Construction type: Built-in Integrated Cleaning system: No Dimensions: 888 x 594 x 550

Dimensions of the packed product (HxWxD) (mm): 960 x 690 x 660

Control Panel Material: Glass Door Material: Glass Net weight (kg): 50.993 Usable volume of cavity (I): 71

Cooking method: Conventional heat, Full width grill, Hot Air, Hotair

gentle, Hot air grilling

Temperature control: mechanical Number of interior lights: 1 Approval certificates: CE, VDE EAN code: 4242003803233 Energy efficiency rating: A

Energy consumption per cycle conventional (2010/30/EC): 1.02 Energy consumption per cycle forced air convection (2010/30/EC):

Energy efficiency class (2010/30/EC) - cavity 2: B

Energy consumption per cycle conventional - cavity 2 (2010/30/EC) :

0.83

Energy efficiency index (2010/30/EC): 95.3

Energy efficiency index cavity 2 (2010/30/EC): 120.3

Connection rating (W): 6200

Current (A): 32 Voltage (V): 220-240 Frequency (Hz): 50

Plug type: fixed connection, no plug





iQ500, Built-in double oven, Stainless steel MB535A0S0B

Features

Design

- LCD Display (white)
- Stainless steel control dial, lightControl: intuitive operation thanks to the illuminated dials, round
- Electronic oven clock timer
- Bar handle
- lightControl: intuitive operation thanks to the illuminated dials
- Interior halogen light

Features

- Control panel lock
- Automatic start
- Heating-up indicator
- cookControl
- •

Top oven additional features

- Full glass inner door
- Cavity volume: 34 l
- EcoClean Direct :ceiling, back panel, side liners
- Cavity (inner surface) top: Enamel grey
- Door hinge small cavity: Drop down oven door

Main oven additional features

- Cavity volume: 71 litres
- EcoClean Direct : back panel
- Full glass inner door
- cookControl, 10
- Cavity (inner surface) bottom: enamel grey
- Door hinge big cavity: Drop down oven door
- 5 shelf positions in oven
- Oven with 4 heating methods: conventional oven, Large-area grill, Small area grill, bottom heat
- Temperature range 50 °C 275 °C
- Oven with 5 heating methods: 3D hot air, conventional top & bottom heating, hot air grilling, full width grill, Hotair gentle
- Temperature range 50 °C 275 °C
- fast preheat function

Accessories

- 3 x combination grid, 1 x universal pan
- 1 varioClip rail, Stop function

Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): B (at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode: 0.83 kwh
- Number of cavities: Top Cavity
- Heat source: electrical
- Energy efficiency rating (acc. EU Nr. 65/2014): B (at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode: 0.83 kWh
- Energy consumption per cycle in fan-forced convection mode: 0.81 kwh
- Number of cavities: Main Cavity
- Heat source: electrical

- Total connected load electric: 6.2 KW
- Nominal voltage: 220 240 V
- Niche dimension (hxwxd): 875 mm 888 mm x 560 mm 568 mm x 550 mm
- Appliance dimension (hxwxd): 888 mm x 594 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



iQ500, Built-in double oven, Stainless steel MB535A0S0B

Back panel open 19.5 145 875+13 min. 891 180 888 max 50 560+10 594 Space for appliance connection 320 x 115 measurements in mm measurements in mm 18 🛊 888 774 550