

Product Finish: Antique Brass

Product code: AT1031
EAN13 barcode: 5060048380309



Note: the image shown may not reflect the product finish, chrome finish is typically depicted.


Product features:

- Metal & acrylic handle construction
- Supplied with adjustable centre inlets
- Fixing kit designed for thicker surface depths
- Quarter turn handle action for precise flow control
- Custom designed for lower to mid pressures

Additional information / Parts included:

130 - 230mm centres

Product dimensions:



- **Overall Height / projection:** 400 mm
- **Exit reach:** 235 mm
- **Exit height:** 260 mm
- **Centre distance(s):**

- **Base diameter(s):** 50 mm
- **Recommended hole diameter:** Ø 35 mm
- **Max. surface depth:** 80 mm

- **Spout diameter:** 20 mm
- **Spout aerator size:** 18f

Packaged properties:

Box length: 575mm

Box depth: 75mm


Box width: 355mm

Units per outer: 5

Tap only weight: 2.03kg

Boxed weight: 2.66kg

Product flow characteristics:



- **Min / Max water pressure:** 0.20 / 5.50 bar
- **Recommended / Max water temperature:** 46°C / 70°C
- **Part G - Mixed flow rate at 3 bar (litres / min):** 31.00

- **Control valve type:** Ceramic disc QT
- **Product flow characteristics:** Single flow
- **Non return valve(s):** Integral to hot & cold inlets

- **Aerator type:** Plastic mesh diffuser
- **Accepts revolve / spray areator:** No
- **Spout connection method:** Locking collar

- **Tail pipe inlet / outlet size:** 1/2" BSP Male
- **Inlet pipe type / length:** fixed threaded inlets / 120 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year