

Product Finish: Chrome

Product code: AT2160
EAN13 barcode: 5060344159739




Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product features:

- Supplied complete with flexible tail pipes for fast simple fitting
- Single lever control for effortless single handed control
- Additional jet spray function
- Minimalist planate design form
- Urban industrial styling

Additional information / Parts included:

Product dimensions:




- **Overall Height / projection:** 461 mm
- **Exit reach:** 225 mm
- **Exit height:** 201 mm
- **Centre distance(s):**
- **Base diameter(s):** 50 mm
- **Recommended hole diameter:** Ø 35 mm
- **Max. surface depth:** 40 mm
- **Spout diameter:** 24 mm
- **Spout aerator size:** M22 male

Packaged properties:

- Box length:** 575mm
- Box depth:** 80mm
- Box width:** 350mm
- Units per outer:** 5
- Tap only weight:** 2.00kg
- Boxed weight:** 2.75kg

Product flow characteristics:



- **Min / Max water pressure:** 1.00 / 5.5 bar
- **Recommended / Max water temperature:** 46°C / 70°C
- **Part G - Mixed flow rate at 3 bar (litres / min):** 08.49
- **Control valve type:** Single lever ceramic cartridge
- **Product flow characteristics:** Single flow
- **Non return valve(s):** Integral to sprayhead and Cold inlet
- **Aerator type:** Amfag aerator dual jet
- **Accepts revolve / spray areator:** No
- **Spout connection method:** Grub screw
- **Tail pipe inlet / outlet size:** M8 / 1/2" Male (Hot), 1/2" Female (Cold)
- **Inlet pipe type / length:** flexible stainless braided hose / tbc mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year