


Product Finish: Chrome Product code: PT1122



PRONTEAU tap features:

- Stylish 3 way mixer tap delivering domestic hot, cold and heated 98° (variable selctable) filtered water
- Pull around functionality with spray feature for domestic hot and cold
- Dedicated steaming hot water outlet on tap crossbar
- The dual stage handle mechanism on the hot handle has been designed with safety and ease of use in mind
- Features an energy saving cold start valve as standard
- 360° cool touch spout thanks to centrally insulated steaming water channel
- 5 Year Warranty*



Overall Height / projection: 515 mm

Exit spout reach: 245 mm


Exit spout height: 274 mm

Base diameter(s): 48 mm

Recommended hole diameter: Ø35 mm

• Max. surface installation depth: 50 mm

 Cold start valve allows installation close to backsplashes (handles do not rotate backwards)



PRONTEAU flow information and connectivity:

- Min cold water pressure requirement: 1.5 bar
- Min hot water pressure requirement: 1.20 bar
- Recommended / Maximum (domestic) hot water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres/min): 7.70
- Control valve type: 1 x 1/2" Ceramic disc QT, 1 x Single lever 35mm
- Product flow characteristics: (H&C/Boiling) dual flow
- Hot and Cold inlets: Flexible hose connections supplied
- Non return valve(s): Yes, integral to cold inlet flexi hose only

Care instructions and Warranty Summary*

- Clean the tap regularly as required, using a mild soap and damp cloth, do not use any other cleaners, regular cleaning will prevent the build-up of lime scale and dirt
- Maintain the heater according to the user guide, for example replace filter and descale when required.
- Mixertap materials and workmanship defects warranted for 5 years
- Proboil2X materials and workmanship defects warranted for 2 years
- Mixertap valves and working parts warranted for 5 years
- Surface finish warranty defects warranted for 1 year
- All o-rings, hoses & gaskets warranted for 1 year